



# Enhancing Our Life With Green Energy







# About Us

Light Vision offer various range of LED lighting products for architectural, offices, residential, shopping malls, showroom etc. We are able to provide solution, consultation and design to our customer in order to create the next brilliant lighting masterpiece. At Light Vision, we continue challenging the LED lighting technology in all aspects to create the new products with accomplishment in our R&D team and factory in Taiwan.

We wish to leverage our expertise in LED technology towards a safety and friendly environment and also enrich our life style for better living.







# Product Line

### **LED LAMP Series**

- •12W LED PAR30 Bulb, Base: E26
- •12W LED PAR30L Dimming Bulb, Base: E26
- •14W LED PAR30LA Bulb, Base: E26 (Convention TRIAC dimmer to control output bright)
- •15W LED PAR38 Bulb, Base: E26
- •3W LED MR16 Bulb, Base: GU5.3
- •3W LED GU10 Bulb, Base: GU10
- •5W MR16 Bulb, Base: GU5.3

## **LED Recessed light Series**

- •10W LED Recess Down Light GT26
- •15W LED Recess Down Light GT32
- •10W LED AR111, Base: G53

### **Industry Lighting**

• PL30

### **AC LED**

•10W AC LED Desk Lamp



Low Energy Consumption

No UV or IR Emission

Contain No Mercury

Saving 85% Power

Long Service Life

High Color Rendering Performance

Safety and Environmentally Friendly











Light Vision Corp.
2002 E Locust Ct. Ontario, CA 91764 USA
Website: www.lightvision-led.com

MILL

TEL::+1909-947-0549
FAX:+1626-956-0696
Email: service@lightvision-led.com

# Cleaning Our Life With Green Energy



# LED Lamp

### 12W LED PAR30 Bulb, Base: E26















| MODEL        | BEAM ANGLE   | COLOUR TEMPERATURE                     | INPUTVOLTAGE | WATTAGE | Net Weight | DRIVER   |
|--------------|--------------|--|--------------|---------|------------|----------|
| LVC-LB-PAR30 | 25°/40°/140° | Warm White / Neutral White /Cool White | 120V AC      | 12W     | 215 ± 5 g  | Built-in |

### 12W LED PAR30L Dimming Bulb, Base: E26











APPLICATION: Retail Ceiling Fixture Restaurant Lobby Hallway

Dimming: 100%,75%,50%,25%



FC

c UL us

|               |              |  | Replacet     | raditional 75W Hal | ogen       | LISTED   |
|---------------|--------------|--|--------------|--------------------|------------|----------|
| MODEL         | BEAM ANGLE   | COLOUR TEMPERATURE                     | INPUTVOLTAGE | WATTAGE            | Net Weight | DRIVER   |
| LVC-LB-PAR30L | 25°/40°/140° | Warm White / Neutral White /Cool White | 120V AC      | 12W                | 280 ± 5 g  | Built-in |

### 14W LED PAR30LA Bulb, Base: E26











APPLICATION: Retail

Hallway Church Residential Application



Restaurant Lobby

### Replace traditional 75W Halogen

| MODEL          | BEAM ANGLE   | COLOUR TEMPERATURE                     | INPUTVOLTAGE | WATTAGE | Net Weight | DRIVER   |
|----------------|--------------|--|--------------|---------|------------|----------|
| LVC-LB-PAR30LA | 25°/40°/140° | Warm White / Neutral White /Cool White | 120V AC      | 14W     | 345 ± 10 g | Built-in |

### 15W LED PAR38 Bulb, Base: E26













APPLICATION: Retail Ceiling Fixture Restaurant Lobby Hallway Replace traditional 120W Halogen

FC  $\epsilon$ 

|                  |              |            | 3                                      |              |         |            |          |  |
|------------------|--------------|------------|--|--------------|---------|------------|----------|--|
| MODEL BEAM ANGLE |              | BEAM ANGLE | COLOUR TEMPERATURE                     | INPUTVOLTAGE | WATTAGE | Net Weight | DRIVER   |  |
|                  | LVC-LB-PAR38 | 30°/60°    | Warm White / Neutral White /Cool White | 100-250V AC  | 15W     | 400 ± 5 g  | Built-in |  |















# LED Lamp

### 3W LED MR16 Bulb, Base: GU5.3









APPLICATION:

Villa Meeting Room Hotel Stairway & hallway Restaurant lighting F© ( €


Replace traditional 35W Halogen

| ,             |            |   | Replaceti    | auitional 33W H | alogeli    |                  |
|---------------|------------|---|--------------|-----------------|------------|------------------|
| MODEL         | BEAM ANGLE | COLOUR TEMPERATURE                          | INPUTVOLTAGE | WATTAGE         | Net Weight | DRIVER           |
| LVC-LB-3WMR16 | 38°        | Warm White / Neutral White /Cool White/Blue | 12V AC       | 3W              | 40 ± 5 g   | Remot (Excluded) |

### 3W LED GU10 Bulb, Base: GU10







APPLICATION:

Entertainment lighting Bollards/Security Lighting Architectural Lighting Interior Commercial Lighting


 $\epsilon$ 

### Replace traditional 35W Halogen

| MODEL         | BEAM ANGLE | COLOUR TEMPERATURE                     | INPUTVOLTAGE | WATTAGE | Net Weight | DRIVER            |
|---------------|------------|--|--------------|---------|------------|-------------------|
| LVC-LB-3WGU10 | 38°        | Warm White / Neutral White /Cool White | 100-250V AC  | 3W      | 60 ± 5 g   | Remote (Excluded) |

### 5W MR16 Bulb, Base: GU5.3









APPLICATION:

Entertainment lighting Bollards/Security Lighting Architectural Lighting Interior Commercial Lighting Landscape Lighting

F© ( £

Replace traditional 35W Halogen

| MODEL         | BEAM ANGLE | COLOUR TEMPERATURE                          | INPUTVOLTAGE | WATTAGE | Net Weight | DRIVER           |
|---------------|------------|---|--------------|---------|------------|------------------|
| LVC-LB-5WMR16 | 10°/38°    | Warm White / Neutral White /Cool White/Blue | 13V AC       | 5W      | 75 ± 5 g   | Remote(Excluded) |

# AC LED

### 10W AC LED Desk Lamp



| AC LED 10W Desk Lamp Specifications |              |                         |  |  |  |  |
|-------------------------------------|--------------|-------------------------|--|--|--|--|
| Model No.                           | LVC-LB-ACLED | Luminance Flux          | Min.800Lux   |  |  |  |
| Rated Voltage                       | 110V/220V    | Dimensions              | 7.09inch*10.83inch*16.14inch(Box)                          |  |  |  |
| Power Consumption                   | 10W          | The appearance of color | Silver White   |  |  |  |
| Specifications                      | 10W AC LED   | Applications            | Two stage switch,with a table lamp and nightlight function |  |  |  |



Light Vision Corp.

2002 E Locust Ct. Ontario, CA 91764 USA
Website: www.lightvision-led.com

TEL: +1909-947-0549 FAX: +1626-956-0696

Email: service@lightvision-led.com

<<<<<<





# LED Recessed Downlight
















APPLICATION:

Hotels Lobby & Restaurants Dwelling Houses Showcases & Showrooms Shops & Shopping Centers

Bank Lobby Retail Outlets


Replace 75W Incandescent Lamp



|             |                  | 301 10 30 301                          |                |         |            |          |
|-------------|------------------|--|----------------|---------|------------|----------|
| MODEL       | BEAM ANGLE       | COLOUR TEMPERATURE                     | INPUTVOLTAGE   | WATTAGE | Net Weight | DRIVER   |
| LVC-LB-GT26 | 25°/40°/60°/140° | Warm White / Neutral White /Cool White | DC 500mA / 24V | 10W     | 370 ± 5 g  | Included |

### 15W LED Recess Down Light GT32





APPLICATION: Hotels Lobby & Restaurants Dwelling Houses

Showcases & Showrooms

**Shopping Centers** Bank Lobby Retail Outlets

FC (E

Replace120WIncandescent Lamp

MODEL **BEAM ANGLE COLOUR TEMPERATURE INPUTVOLTAGE** WATTAGE Net Weight DRIVER 25°/40°/60°/140° Warm White / Neutral White /Cool White DC 700mA / 24V  $390 \pm 5 g$ LVC-LB-GT32 15W Included

10W LED AR111, Base: G53


















Entertainment linghting Architectural Lighting Landscape


Bollards/Security Lighting Interior Commercial Lighting



|              |                  |  | Replace 75W Incandescent Lamp |         |            |          |  |
|--------------|------------------|--|-------------------------------|---------|------------|----------|--|
| MODEL        | BEAM ANGLE       | COLOUR TEMPERATURE                     | INPUTVOLTAGE                  | WATTAGE | Net Weight | DRIVER   |  |
| LVC-LB-AR111 | 25°/40°/60°/140° | Warm White / Neutral White /Cool White | 12V AC/DC                     | 10W     | 190 ± 5 g  | Included |  |

### 30W LED PL30





APPLICATION: Architectural Lighting Interior Commercial Lighting

Dimension (inch) W/L/H 24×24×2 1/4"



|             |                          |  |               |         |            |          | 1 |
|-------------|--------------------------|--|---------------|---------|------------|----------|---|
| MODEL       | BEAM ANGLE               | COLOUR TEMPERATURE                     | INPUTVOLTAGE  | WATTAGE | Net Weight | DRIVER   |   |
| LVC-LB-PL30 | Horizon 90° Vertical 70° | Warm White / Neutral White /Cool White | 100VAC~240VAC | 30W     | 2.1kg± 2kg | Included |   |

Light Vision Corp. 2002 E Locust Ct. Ontario, CA 91764 USA Website: www.lightvision-led.com

TEL: +1909-947-0549 FAX: +1626-956-0696

**<<<<<<** 

Email: service@lightvision-led.com

